

## AQUEOUS BF700-- M/P BACKLIT FRONT GLOSSY 215

M/P BACKLIT FRONT GLOSSY 215 delivers impressive colour reproduction, a high transmission OD over 3.5 with New pigment inks and soft color gradients with high resolution as well as excellent contour definition. The very high level of colour saturation achieved allows a wider colours combined with very deep blacks guarantee an exceptionally three-dimensional picture and a uniquely luminous quality. Consist are translucent polyester film with glossy microporous coating for backlit application.

It has advantages of water proof, instant dry and sharp expression of details due to microporous coating.  
Micro porous technology acheives an unbeatably good photographics quality on all wellknown inkjet printing system.  
It is also easy to install because of very good rigidity and flatness of 13 mil base polyester film.

### APPLICATION

Indoor Light box application.  
Cosmetic luminous advertising display  
Fashion luminous advertising display  
Department store luminous advertising display




### SPECIFICATION

Caliper	215 micron (8.6 mil)
weight	285g
Base material	Polyester film
Surface	High Glossy
Width	36", 50", 60"
Length	30m (100 ft)
Core	2"

### COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

#### Ink Compatibility

Dye	Pigment	New Pigment
		

#### Printer Compatibility

Most Aqueous Printing system, Especially New Printers  
HP Z-Series, Canon IPF Series, Epson, Rolan Mimaki, Mutoh

### TECHNICAL DATA

Caliper	215 micron	ASTM D645
Gloss	60° : 35 / 85° : 80	ASTM D2457
L.a.b	85 / -1 / -0.5	ANSI T (D50/2°/Abs/No)

### GUIDELINES

#### Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%  
Use care in handling printed material, surface susceptible to abrasion  
To optimize the printing quality, printer need to be set for highest print quality.

#### Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.

#### Storage:

It is recommended to store in the closed original packing in a cool and dry environment  
Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

#### Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.