

Nazdar[®] 1300 Series Digital Imaging Inks are designed as a mild solvent ink sets for use in printers utilizing Epson DX-4, 5, 6 & 7 print heads.

v 10 EN

Ref: v10 EN

Primary Features & Substrates

Features

- Excellent general use mild solvent ink set
- Revised color match to latest Mimaki SS2 inks.
- Can be profiled for extra wide gamut.
- Compatible with OEM ink (SS2)
- Reliable unattended printing
- Substantial savings over OEM ink

Substrates

- Self-Supporting flexible and pressure sensitive vinyl.
- Banner Material
- Blue back paper
- Backed mesh

Ink Handling

All personnel mixing and handling these products must wear gloves and eye protection. Clean up all spills immediately. If ink does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or flush solution). Wash the affected area with soap and water. Consult the Nazdar[®] 1300 Series Material Safety Data Sheet for further instructions and warnings.

Ink Changeover

When changing from Mimaki SS2 original ink cartridges to Nazdar 1300 series cartridges operators should remove the empty OEM ink cartridge and replace with a Lyson ink cartridge and continue printing. This can be carried out either one color at a time or all colors together.

No ink fills are required.

For conversions from inks sets other than Mimaki SS2 or bulk feed systems please consult www.nazdar.com.

Clean Up

Use item number LWS1300FF Flush Solution for the most effective cleanup of ink spills and cleaning of jet assemblies. Avoid contact with skin. Wear approved safety glasses and appropriate gloves when using Maintenance Solution. Consult MSDS for further safety precautions.

Storage/Shelf Life

Storage and transportation of ink and cleaning solutions should be carried out between 5° - 25°C (41° - 77°F). Ink and cleaning solutions should always be kept away from heat, sparks, and flames. If stored or transported at a different temperature, the ink should be allowed to reach room temperature before calibration or printing. This may have an adverse effect on performance and will affect any warranties given by Nazdar[®].

Recommended shelf life of this product is 15 months from the date of manufacture when stored under preferred conditions.

Ink Performance

Outdoor Durability

Nazdar[®] 1300 Series Inks are designed for maximum outdoor resistance to color fade and chemical attack caused by the combined effects of UV degradation and environmental pollution.

Each color is formulated with durable long-term outdoor pigments. When Nazdar[®] 1300 Series Inks are used with proper color management, color variance of the original print density will be minimal over a period of 24 months for vertical outdoor exposure.

To ensure the color properties of Nazdar[®] 1300 Series inks do not change during outdoor exposure, it is important to use proven substrates (flexible vinyls and pressure sensitive vinyls) that do not "yellow" or vary from their original white cast when exposed outdoors. All Nazdar[®] 1300 Series Inks are formulated for maximum adhesion to an extensive range of unsupported and pressure sensitive vinyls. Always pretest for acceptable adhesion prior to production.

Digital Solvent Inkjet

Nazdar 1300 Series Solvent Inkjet Ink



v 10 EN

Ref: v10 EN

Environmental Operating Parameters

Temperature:

- 66 ° F – 80 ° F [19 ° C – 27 ° C]

Humidity:

- Optimum: 40% - 60% (non-condensing)
- Operational: 30% - 70% (non-condensing)

Nazdar Quality Statement

Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating and production procedures. While technical information and advice on the use of this product is provided in good faith, the user bears sole responsibility for selecting the appropriate product for their end use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life cycle from printing, post print processing, and shipment to end use. This product has been specially formulated for digital printing, and it has not been tested by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.

Based on information from our raw material suppliers, these products are formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

Validated Equipment

Nazdar® 1300 Series Inks are designed for use in for use in printers utilizing Epson DX-4, 5, 6 & 7 print heads.

Manufacturers Product Offering

All colors listed below are available in 440ml cartridges and 1 liter containers. Flushing solution is available in 220ml cartridges and 1 & 5 liter containers. Contact your Nazdar distributor for product availability and offering.

Inks

Item Number	Color
LWS1300CY	Cyan
LWS1300MA	Magenta
LWS1300YE	Yellow
LWS1300KK	Black
LWS1300LC	Light Cyan
LWS1300LM	Light Magenta

Flush

Item Number	Color
LWS1300FF	1300 Series Flush Solution

Nazdar Ink Technologies Offices Worldwide

Nazdar Ink Technologies -World Headquarters
8501 Hedge Lane Terrace
Shawnee, KS 66227-3290 USA
Toll Free US: 866-340-3579
Tel: +1 913-422-1888
Fax: +1 913-422-2296
E-mail: custserv@nazdar.com
Technical Support E-mail: InkAnswers@Nazdar.com

Nazdar Limited – EMEA
Barton Road, Heaton Mersey
Stockport, England SK4 3EE
Tel: + (44) 0-161-442-2111
Fax: + (44) 0-161-442-2001
UK Technical Service E-mail: technicalservicesuk@nazdar.com

Nazdar – China
Room 17-04, Silver Centre
1388, North Shan Xi Road
Shanghai 130060 China
Tel: 86-13818301261
E-mail: aspac@nazdar.com

Nazdar – Asia Pacific
10, Changi South Street 3 #01-01
Singapore 486147
Tel: +65-65434920
Fax: +65-65433690
E-mail: aspac@nazdar.com

Digital Solvent Inkjet