HP Latex 375 Printer



Gain more unattended printing at lower cost of operation with this fullfeature 64-inch printer



Expand your applications-beat client expectations

- Get higher margins³ printing on traditional signage substrates and beyond—even textiles¹ –up to 64 inches.
- Reach more indoor spaces, like healthcarewater-based HP Latex Ink prints are odorless.¹
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi.

Same-day delivery with more unattended production

- High quality at high speeds—334 ft² (31 m²)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer.⁴
- Increase unattended printing with confidence change 3-liter HP Latex Ink cartridges while the printer runs.
- Reach production speeds and avoid wait timeprints come out completely dry and ready to finish and deliver.
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner.²

Keep running costs low with 3-liter ink cartridges

- Help reduce your cost per print with costeffective, 3-liter HP 871 Latex Ink Cartridges.³
- Reduce time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic.⁵
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads.
- Monitor your printer remotely with the free HP Latex Mobile app.⁶

For more information, please visit http://www.hp.com/go/latex375

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Performance may vary depending on media-for more information, see http://www.hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles. Odorless prints: there is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. ² Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE

J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance. ³ For the HP Latex 375 Printer using cost-effective, high-capacity HP 871 3-liter Latex Ink Cartridges compared to the HP Latex 365 Printer using HP 831 775-ml Latex Ink Cartridges.

 ⁴ Banner-quality prints in outdoor (4-pass 4-color) mode.
 ⁵ ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

⁶ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

Technical specifications

| Print | |
|---|---|
| Printing modes | 91 m²/hr - Max Speed (1 pass) 31 m²/hr - Outdoor High Speed (4 pass) 23 m²/hr - Outdoor Plus (6 pass) 17 m²/hr - Indoor Quality (8 pass) 14 m²/hr - Indoor High Quality (10 pass) 6 m²/hr - Backlits, Textiles, and Canvas (16 pass) 5 m²/hr - High Saturation Textiles (20 pass) |
| Print resolution | Up to 1200 x 1200 dpi |
| Ink types | Water-based HP Latex Inks |
| Ink cartridges | 7 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer) |
| Cartridge size | 3 L, 775 ml |
| Printheads | 6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer) |
| Long-term print-to-print repeatability | t Average \leq 1 dE2000, 95% of colors \leq 2 dE2000 ¹ |
| Media | |
| Handling | Roll feed, take-up reel, automatic cutter (for vinyl, paper-based media, backlit polyester film) |
| Media types | Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fabrics, mesh, textiles ² |
| Roll size | 254 to 1625-mm rolls (580 to 1625-mm rolls with full support) |
| Roll weight | 42 kg |
| Roll diameter | 250 mm |
| Thickness | Up to 0.5 mm |
| Applications | Banners; Displays; Double-sided banners; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Traffic signage |
| Connectivity | |
| Interfaces | Gigabit Ethernet (1000Base-T) |
| Dimensions (w x d | x h) |
| Printer | 2561 x 840 x 1380 mm |
| Shipping | 2795 x 760 x 1705 mm |
| Operating area | 2761 x 1840 mm |
| Weight | |
| Printer | 231.5 kg |
| Shipping | 231.5 kg 333.5 kg |
| What's in the box | HP Latex 375 Printer, printheads, maintenance cartridge, ink collector, output platen protector, printer stand, spindle, take-up reel, variable front tension kit, loading accessory, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords |
| | |
| Environmental ran | ges |
| Environmental ran | |
| | |
| Operating temperature | 15 to 30°C |
| Operating temperature Operating humidity Acoustics | 15 to 30°C 20 to 80% RH (non-condensing) |
| Operating temperature Operating humidity Acoustics Sound pressure | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power | 15 to 30°C 20 to 80% RH (non-condensing) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Consumption Requirements Certification | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |
| Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety | 15 to 30°C 20 to 80% RH (non-condensing) 55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep) |

Ordering information

| Product | |
|---------|---|
| V8N83A | H |

| 183A | HP Latex 375 Printer |
|------|----------------------|
| | |

Accorcorios

| Accessories | | | | | |
|--|---|--|--|--|--|
| F0M56A F0M58A F0M59A F0M63A F0M64A T4E58B T7U74A | HP Series 300 64-in Printer 2-in Spindle HP Series 300 64-in Printer 3-in Spindle HP Latex User Maintenance Kit HP Series 300 Media Loading Accessory HP Series 300/500 Edge Holder Kit HP Latex Media Saver Kit HP Series 300/500 Ink Collector Foam Kit | | | | |
| Original HP | Original HP printing supplies | | | | |
| C2677A (Z678A (Z679A (Z680A (Z681A (Z688A (Z689A (Z690A (Z691A (Z691A (Z692A (Z693A (Z706A G0/79B G0/80B | HP 831 Cyan/Black Latex Printhead HP 831 Yellow/Magenta Latex Printhead HP 831 Light Magenta/Light Cyan Latex Printhead HP 831 Latex Optimizer Printhead HP 831 B 775-ml Back Latex Ink Cartridge HP 831B 775-ml Cyan Latex Ink Cartridge HP 831B 775-ml Magenta Latex Ink Cartridge HP 831B 775-ml Yellow Latex Ink Cartridge HP 831B 775-ml Light Cyan Latex Ink Cartridge HP 831B 775-ml Light Cyan Latex Ink Cartridge HP 831B 775-ml Light Magenta Latex Ink Cartridge HP 831B 775-ml Light Magenta Latex Ink Cartridge HP 831P 375-ml Light Magenta Latex Ink Cartridge HP 831P 375-ml Light Cyan Latex Ink Cartridge HP 831P 3-filter Cyan Latex Ink Cartridge HP 871B 3-liter Cyan Latex Ink Cartridge | | | | |
| G0Y80B G0Y81B G0Y82B G0Y83B G0Y84B G0Y85A | HP 871B 3-liter Magenta Latex Ink Cartridge HP 871B 3-liter Yellow Latex Ink Cartridge HP 871B 3-liter Black Latex Ink Cartridge HP 871B 3-liter Light Cyan Latex Ink Cartridge HP 871B 3-liter Light Magenta Latex Ink Cartridge HP 8713-liter Light Magenta Latex Ink Cartridge | | | | |

Original HP large format printing materials

HP Permanent Gloss Adhesive Vinyl (REACH certified³) HP PVC-free Durable Smooth Wall Paper (REACH³, FSC^{®5}, UL GREENGUARD GOLD certified⁶) HP Premium Poster Paper⁴ (FSC[®] certified⁵)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U9JF1E HP 2 year NBD with Defective Media Retention U9JF2E HP 3 year NBD with Defective Media Retention U9JF5PE HP 1 year Post Warranty NBD with Defective Media Retention U9JF6PE HP 2 year Post Warranty NBD with Defective Media Retention

ECO highlights

- Better for printing companies/operators—no special ventilation or HAPs¹ Better for the end-customer, more differentiation—odorless prints reach more indoor spaces² Better for the environment—HP designs end-to-end sustainability into large-format printing HP Latex Inks are UL GREENGUARD GOLD Certified³

Please recycle printing hardware and eligible printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.
² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
³ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.uc.om/gg or http://www.greenguard.org.
⁴ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT registered where applicable/supported. See http://www.epeat.net for registration status by country.

¹ Reflective measurements on a 943 color target under CIE standard illuminant DSO, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.
² Performance may vary depending on media—for more information, see http://www.hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The optional ink collector is required for porous textiles.
³ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published as HP Printing Products and Consumable Supplies.
⁴ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.
⁵ BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions.
⁶ UL GREENGUARD OLD Lerdification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.lcom/gg or http://www.greenguard.org.



