

TECHNICAL DATA SHEET
BEELITE 3D

Height/Dimensions		1200x2400	1200x3000	1600x2400	1600x3000
10	[mm]	122225	122781	122228	122231
16	[mm]	122226	122782	122229	122232
Squareness	[mm]	±2	±2	±3	±3

Tolerances		
Length	[mm]	± 3
Width	[mm]	± 2
Thickness	[mm]	± 0,3


Thickness		10	16
Weight	[kg/m ²]	1,8	2,0

Parameter	All thicknesses	
Liner		White Clay Coated
Core		Recycled paper
Recyclability	[%]	100
Moisture content	[%]	<11
Compression resistance	[ton/m ²]	50
Shipping units		Maximum 2 pallets on top of each other
Storage instructions		Temperature 8-25°C, humidity 55-65%
Whiteness	[%]	92 (iso 11475)
Brightness	[%]	82 (iso 2470-1)
Smoothness PPS10	[µm]	3,5 (iso 8791-4)
Gloss	[%]	49 (iso 8254-1)
Plotter possibilities		V-notch
Printability		Suited for digital printing / screen printing
Date last update		19/05/2014 - DiAS 56203
Application		Sustainable and product-carrying solutions
		(Limited) reuse possible, medium term applications
		(Limited) reuse possible, medium term applications

Beelite nv/sa

 +32 (0)56 78 88 88
 info@beelite.be
 www.beelite.be

 Admin: Beneluxpark 35 - B-8500 Kortrijk - Belgium
 Plant: Avenue Anne Franck 5 - B-7700 Mouscron - Belgium
 BTW/TVA BE 0837.025.965 RPR/RPM Tournai


 Ask for our custom sized pannel service

