

TECHNICAL DATA SHEET
BEELITE 2D

Height/Dimensions		1200x2400	1200x3000	1600x2400	1600x3000
10	[mm]	121100	121102	121101	121103
16	[mm]	121118	122786	121632	121119
Squareness	[mm]	±2	±2	±3	±3

Tolerances		
Length	[mm]	± 3
Width	[mm]	± 2
Thickness	[mm]	± 0,3

Thickness		10	16
Weight	[kg/m ²]	1,2	1,5

Parameter	All thicknesses	
Liner		White fully coated
Core		Recycled paper
Recyclability	[%]	100
Moisture content	[%]	<11
Compression resistance	[ton/m ²]	25
Shipping units		Maximum 2 pallets on top of each other
Storage instructions		Temperature 8-25°C, humidity 55-65%
Whiteness	[%]	93,5 (iso 5631-1)
Brightness	[%]	85 (iso 2470-1)
Smoothness PPS10	[µm]	1 (iso 8791-4)
Gloss	[%]	40 (iso 8254-1)
Plotter possibilities		V-notch
Printability		Suited for digital printing / screen printing
Date last update		19/05/2014 - DiAS 56204
Application		Promotional and decorative applications, single use
		Short term, small to medium sized applications

Beelite nv/sa

 +32 (0)56 78 88 88
 info@beelite.be
 www.beelite.be

 Admin: Beneluxpark 35 - B-8500 Kortrijk - Belgium
 Plant: Avenue Anne Franck 5 - B-7700 Mouscron - Belgium
 BTW/TVA BE 0837.025.965 RPR/RPM Tournai


 Ask for our custom sized pannel service

