

SOLVENT **AE110--**

ECO-SOL ARTIST PAPER MATTE 230

With specialized coating layer for ecosol ink, ECO-SOL ARTIST PAPER MATTE 230g is designed to meet the need of long term display with brilliant colors and high image resolution with Eco Solvent & Latex printing system.

Moreover, this paper provides cost effective solutions by using multi purpose for photo-quality printing with long durability of indoor/outdoor installation.

It is ideal for POSTER application with its 230g weight of an artist paper, elegant gloss and a high ink absorption. With its unique textured base surface, this paper also can be offered for GRAPHIC ART applications.

APPLICATION

Photo realistic prints, Fine Art Reproduction
Display such as Posters, billboards, kiosks
Point-of-purchase printing

LATEX PRINTING MEDIA (NEW PRINTER APPLICATION)


SPECIFICATION

Caliper	195 micron (7.8 mil)
weight	230g
Base material	Paper
Surface	Matte
Width	36", 50", 54", 60"
Length	50m (165 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility



Printer Compatibility

Most Solvent & Eco Solvent Printing system: LATEX & HP, Epson, Roland, Mimaki, Mutoh, Seiko, Océ

TECHNICAL DATA

Caliper	192micron	ASTM D645
Gloss	60° : 87.7 / 85° : 92.1	ASTM D2457
L.a.b	85 / 0 / -6	ANSI T (D50/2°/Abs/No)

GUIDELINES

Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
It is recommended to set up pre and post heaters around 30°C(86°F).
It is necessary to dry up and not to overlap the printed material before drying up.

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.