

ColorPainter M-64s LCIS success coming around!



WX ink -used with **ColorPainter M-64s-LCIS** has been accepted in the list of materials which meet the chemical requirements of **Nordic Ecolabel** certification for printing companies. The **Nordic Ecolabel**, also known as Nordic Swan, is a comprehensive Scandinavian ecolabel that -for more than 25 years- sets highest environmental demands for the products and services evaluated. The ecological footprint of each product is being assessed. The label acknowledges that print products or print service providers have been proved to be ecologically sustainable from raw material to waste. **ColorPainter M-64s LCIS'** eco solvent **WX ink** meets the stringent **Nordic Ecolabel** criteria for print product providers.



SX, SX 3M™, WX inks by OKI have achieved **GREENGUARD Gold** Certification, UL 2818-2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings. **GREENGUARD Gold Certification** helps manufacturers create – and consumers identify – products with low chemical emissions, thus improving air quality in the environments in which they are used. GREENGUARD Certification is part of ULTM Environment, a business unit of UL (Underwriters Laboratories). GREENGUARD certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage.



Seiko Instruments GmbH
Siemensstr. 9
D-63263 Neu-Isenburg
Tel.: +49-6102-297 100
Fax: +49-6102-297 50 100

PRESS RELEASE

Neu-Isenburg, February 18th 2015

Seiko Instruments' WX ink accepted in Nordic Ecolabel product list

Seiko Instruments's WX ink -used with ColorPainter M-64s LCIS has been accepted in the list of materials which meet the chemical requirements of Nordic Ecolabel certification for printing companies.

The Nordic Ecolabel, also known as Nordic Swan, is a comprehensive Scandinavian ecolabel that -for more than 25 years- sets highest environmental demands for the products and services evaluated. The ecological footprint of each product is being assessed. Print products or print service providers according such a label have been proved to be ecologically sustainable from raw material to waste.

Seiko Instruments' eco solvent WX ink is now one of those materials that meet the stringent Nordic Ecolabel criteria for print product providers.

About Seiko I Infotech Inc. and Seiko Instruments GmbH

Seiko I Infotech Inc. (SIIT) is a leading company in wide-format printing technology, and is a subsidiary company of Seiko Instruments Inc. (SII), headquartered in Chiba, Japan. SIIT develops and manufactures precision-engineered wide-format printing systems specifically for the sign, graphics, CAD and GIS markets that provide industry-leading productivity and image quality. SIIT and its worldwide network of authorized distributors and dealers, provides complete printing solutions including wide-format printers, inks, media, software, installation, support, knowledge and training. Seiko Instruments GmbH is the European sales subsidiary of the Japanese manufacturer Seiko Instruments Inc. (SII) for wide format printers.

Contact:

Seiko Instruments GmbH
Stephanie Rohn
Product Manager - Wide Format Printer
stephanie.rohn@seiko-instruments.de

CERTIFICATE OF COMPLIANCE



Seiko I Infotech Inc.

WX Ink cartridge

70679-420

Certificate Number

09/30/2015 - 09/30/2016

Certificate Period

Certified

Status

UL 2818 -2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.

Building products and Interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V.1.1-2010 using the applicable exposure scenario(s).



Environment

GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC ^(A)	-	0.22	mg/m ³
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m ³
Total Aldehydes ^(B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m ³
Particle Matter less than 10 µm ^(C)	-	20	µg/m ³
1-Methyl-2-pyrrolidinone ^(D)	872-50-4	160	µg/m ³
Individual VOCs ^(E)	-	1/2 CREL or 1/100th TLV	-

- (A) Defined to be the total response of measured VOCs falling within the C₆ – C₁₆ range, with responses calibrated to a toluene surrogate.
- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- (C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.
- (D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m³/day
- (E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.1 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



Environment