

PREGASOL P (paste)

1. DESCRIPTION

PREGASOL P is a ready to use emulsion reclaimer for decoating of polymer-based direct emulsions and capillary films such as Diazo- and SBQ-sensitized emulsions. PREGASOL P is a odorless decoating paste for screens that require prolonged reaction time or where drying of liquid reclaimers is a concern.

2. APPLICATION

Apply the PREGASOL P solution with a soft, clean brush evenly on both sides of the wet screen after the screen has been carefully cleaned of ink residue. Rub the screen gently with a brush to dissolve the emulsion.

After approximately 2 minutes, rinse thoroughly with a strong water spray. A high pressure water spray (1000 - 2000 psi, 40 - 60 bar) may be required for highly water resistant emulsions. Prolonged reaction times are possible and may help in the decoating process.

Ensure that the PREGASOL P solution does not dry on the screen. This can lead to a hardening of the emulsion and the resulting emulsion residues will be extremely difficult to remove.

3. PHYSICAL DATA

Color:	Pink
Consistency:	Paste
Shelflife:	2 years at 68 degrees Fahrenheit (20 degrees celsius)
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
pH value:	>5
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

4. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

PREGASOL P can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

6. PACKAGING

1 quart, 1 gallon, 5 gallon containers

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.